

	<p><b>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable</b></p>	
<p><b>TANK TRAILER SPECIFICATION</b></p>		
<p><b>PRODUCT</b></p>	<p><b>C5 RAFFINATE</b></p>	<p><b>C5 RAFF</b></p>
<p><b>Material Characteristic and immediate hazard</b></p>	<p><b>See Product SDS</b></p>	
<p><b>DOT SPECIFICATION</b></p>	<p>MC 330, MC 331 (QT OR NQT TRAILER)</p>	
<p><b>INSULATION</b></p>	<p>NOT REQUIRED</p>	
<p><b>HEATING CAPABILITIES</b></p>	<p>NOT REQUIRED</p>	
<p><b>GASKET MATERIAL</b></p>	<p>TEFLON , GYLON 3510, BARIUM FILLED TEFLON, VITON F  <b>NOTE:</b> O-RING MATERIAL KALREZ 6375, 6380, 1050LF</p>	
<p><b>CONNECTIONS/FITTINGS</b></p>	<p>STANDARD LPG BRASS FITTING W/CAP. THERE MAYBE SPECIAL REQUIREMENT TO BE RECEIVED FROM LOADING FACILITY</p>	
<p><b>LIQUID CONNECTION</b></p>	<p>STANDARD LPG BRASS FITTINGS WITH/CAP. THERE MAYBE SPECIAL REQUIREMENT TO BE RECEIVED FROM LOADING FACILITY. CONTACT LYONDELLBASELL FOR ANY SPECIAL REQUIREMENTS</p>	
<p><b>VAPOR CONNECTION</b></p>	<p>STANDARD LPG BRASS FITTINGS WITH/CAP. THERE MAYBE SPECIAL REQUIREMENT TO BE RECEIVED FROM LOADING FACILITY. CONTACT LYONDELLBASELL FOR ANY SPECIAL REQUIREMENTS</p>	
<p><b>NITROGEN PADDING</b></p>	<p>NITROGEN PURGED, TRAILER MUST HAVE A 5-7 PSIG NITROGEN PAD UPON ARRIVAL TO LOAD</p>	
<p><b>TANK CLEANLINESS</b></p>	<p>IF NOT DEDICATED TRAILER, A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. <b>NOTE:</b> IF TRAILER IS RE-LOAD/TOP-LOAD, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS ARE REQUIRED AS PROOF THAT THE LAST CONTAINED WAS LYONDELLBASELL MATERIAL.</p>	
<p><b>STRAPPING CHART</b></p>	<p>YES</p>	
<p><b>HOSES</b></p>	<p>HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. <b>PLEASE NOTE:</b> THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE <i>CARRIER INSTRUCTIONS</i> FIELD OF THE LYONDELLBASELL SHIPPING DOCUMENT.</p>	
<p><b>ADDITIONAL APPURTENANCES</b></p>	<p>NONE, CARRIER SHOULD ALWAYS NOTE CARRIER INSTRUCTIONS FIELD ON THE SHIPPING DOCUMENT FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. <b>NOTE:</b> ALL OPENINGS TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH A 1/8" WIRE</p>	
<p><b>OTHER</b></p>	<p>MUST HAVE CURRENT AND MATCHING SAP <i>SHIPPING NOTICE</i>, <i>TRANSWIDE CALL-OFF</i>, OR <i>CARRIER MANIFEST</i> DOCUMENT. <b>**DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELLBASELL OF ANY REQUESTED LIGHT LOADING DUE TO POTENTIAL EXCEEDANCE LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS.</b></p>	
<p><b>PROHIBITED</b></p>	<p>NO ADDITIONAL PERSONNEL UNLESS TEAM DRIVERS, PETS ARE PROHIBITED.</p>	