

| | | |
|---|--|-------------------|
|  | These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable | |
| TANK TRAILER SPECIFICATION | | |
| PRODUCT | CMC LIGHTS SOLVENT | CMC LIGHTS |
| Material Characteristic and immediate hazard | See Product SDS | |
| DOT SPECIFICATION | MC 307, DOT 407, STAINLESS STEEL | |
| INSULATION | PREFERRED BUT NOT REQUIRED | |
| HEATING CAPABILITIES | NOT REQUIRED | |
| GASKET MATERIAL | VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, **DOME GASKET AND OTHER GASKETS, MUST PROVIDE A LEAK TIGHT SEAL PRE AND POST LOADING. ALL OPENINGS TO TRAILER MUST HAVE A SEAL POINT | |
| CONNECTIONS/FITTINGS | ALL MUST BE STAINLESS STEEL, W/DUST CAP, W/SEAL PONTS ON ALL OUTLET OF TRAILER, CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL (MUST HAVE SEAL POINTS). | |
| LIQUID CONNECTION | 3" MALE CAMLOCK, (QUICK CONNECT), W/DUST CAP - BOTTOM REAR LOADER, (CENTER LOADER WILL REQUIRE PRE-APPROVAL BY LYONDELLBASELL). MUST HAVE SEALING CAPABILITIES. NOTE: DELIVERY CUSTOMER MAY HAVE SPECIFIC EQUIPMENT REQUIREMENTS LISTED IN THE CARRIER INSTRUCTIONS FIELD OF THE SHIPPING DOCUMENT. MUST HAVE SEAL POINTS. | |
| VAPOR CONNECTION | 2" MALE CAMLOCK (QUICK CONNECT), W/DUST CAP, WITH PIPING TO GRADE LEVEL, WITH 2" SS ISOLATION VALVE UPSTREAM OF FITTING, (INLINE PRESSURE GAUGE @ GRADE LEVEL PREFERRED). 2" WITH DUST CAP, (MUST BE ABLE TO SEAL), STANDARD 3/4" TOP VAPOR CONNECTION MAY BE ACCEPTABLE. | |
| NITROGEN PADDING | TRAILER MUST HAVE 5-7 PSIG NITROGEN PAD UPON ARRIVAL FOR LOADING. | |
| TANK CLEANLINESS | IF NOT DEDICATED TRAILER, A CLEAN TRAILER MUST BE CLEAN, DRY, AND ODOR FREE. A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. NOTE: IF TRAILER IS RE-LOAD, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS ARE REQUIRED AS PROOF THAT THE LAST CONTAINED WAS LYONDELLBASELL MATERIAL | |
| STRAPPING CHART W/DRIVER | YES | |
| HOSES | HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE <i>CARRIER INSTRUCTIONS</i> FIELD OF THE LYONDELLBASELL SHIPPING DOCUMENT. | |
| ADDITIONAL APPURTENANCES | NONE, CARRIER SHOULD ALWAYS NOTE <i>CARRIER INSTRUCTIONS</i> FIELD OF SHIPPING DOCUMENT FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENING TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL. | |
| OTHER | MUST HAVE CURRENT AND MATCHING SAP <i>SHIPPING NOTICE</i> , <i>TRANSWIDE CALL-OFF</i> , OR <i>CARRIER MANIFEST</i> DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELLBASELL OF ANY REQUESTED LIGHT LOADING; DUE TO POTENTIAL EXCEEDANCE OF LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS. | |
| PROHIBITED | NO ADDITIONAL PERSONNEL UNLESS TEAM DRIVERS, PETS ARE PROHIBITED. | |