

	<b>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable</b>	
<b>TANK TRAILER SPECIFICATION</b>		
<b>PRODUCT</b>	<b>CUMENE</b>	
<b>Material Characteristic and immediate hazard</b>	<b>See Product SDS</b>	
<b>DOT SPECIFICATION</b>	MC 307, DOT 407, STAINLESS STEEL	
<b>HEATING/INSULATION</b>	PREFERRED BUT NOT REQUIRED	
<b>GASKET MATERIAL</b>	TEFLON ROPE, VIRGIN TEFLON, WHITE BUNA, EPDM, <b>**DOME GASKET MUST PROVIDE A LEAK FREE TIGHT SEAL UPON COMPLETION OF LOADING. DOME LID MUST HAVE SEAL POINTS.</b>	
<b>CONNECTIONS/FITTINGS</b>	ALL MUST BE STAINLESS STEEL, W/DUST CAPS W/SEAL PONTNS ON ALL OUTLETS OF THE TRAILER, CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL	
<b>LIQUID CONNECTION</b>	3" MALE CAMLOCK, (QUICK CONNECT), W/DUST CAP - BOTTOM REAR LOADER, (CENTER LOADER REQUIRE APPROVAL). <b>NOTE:</b> CUSTOMER MAY HAVE SPECIFIC EQUIPMENT REQUIREMENTS LISTED IN THE <i>CARRIER INSTRUCTIONS</i> FIELD OF SHIPPING DOCUMENT. MUST HAVE SEAL POINTS.	
<b>VAPOR CONNECTION</b>	2" MALE CAMLOCK (QUICK CONNECT), W/DUST CAP, WITH PIPING TO GRADE LEVEL, WITH 2" SS ISOLATION VALVE UPSTREAM OF FITTING, (INLINE PRESSURE GAUGE @ GRADE LEVEL PREFERRED). 2" WITH DUST CAP, (MUST BE ABLE TO SEAL), STANDARD 3/4" TOP VAPOR CONNTECTION IS ACCEPTABLE	
<b>NITROGEN PADDING</b>	TRAILER MUST HAVE 5-7 PSIG NITROGEN PAD UPON ARRIVAL TO LOAD.	
<b>TANK CLEANLINESS</b>	IF NOT DEDICATED TRAILER, A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. A CLEAN TRAILER MUST BE CLEAN, DRY, AND ODOR FREE. <b>NOTE:</b> IF TRAILER IS RE-LOADING/TOP-LOADING, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS IS REQUIRED TO INDICATE THE SAME PRIOR PRODUCT	
<b>STRAPPING CHART W/DRIVER</b>	YES	
<b>HOSES</b>	HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. <b>PLEASE NOTE:</b> THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE <i>CARRIER INSTRUCTIONS</i> FIELD OF THE LYONDELLBASELL SHIPPING DOCUMENT.	
<b>ADDITIONAL APPURTENANCES</b>	NONE, CARRIER SHOULD ALWAYS NOTE <i>CARRIER INSTRUCTIONS</i> FIELD FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. <b>NOTE:</b> ALL OPENINGS TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL.	
<b>OTHER</b>	MUST HAVE CURRENT AND MATCHING SAP <i>SHIPPING NOTICE</i> , <i>TRANSWIDE CALL-OFF</i> , OR <i>CARRIER MANIFEST</i> DOCUMENT. <b>**DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELLBASELL OF ANY REQUESTED LIGHT LOADING DUE TO POTENTIAL EXCEEDANCE LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS</b>	
<b>PROHIBITED</b>	NO ADDITIONAL PERSONNEL, UNLESS TEAM DRIVERS, PETS ARE PROHIBITED.	

