

	<p>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable</p>	
TANK TRAILER SPECIFICATION		
PRODUCT	ISOBUTYLENE	
Material Characteristic and immediate hazard	See Product SDS	
DOT SPECIFICATION	MC 330, MC 331 (QT OR NQT TRAILER)	
INSULATION	NOT REQUIRED	
HEATING CAPABILITIES	NOT REQUIRED	
GASKET MATERIAL	TEFLON , GYLON 3510, BARIUM FILLED TEFLON, VITON F NOTE: "O" RING MATERIAL KALREZ 6375, 6380, 1050LF	
CONNECTIONS/FITTINGS	STANDARD LPG BRASS FITTING W/CAP. THERE MAYBE SPECIAL REQUIREMENT TO BE RECEIVED FROM LOADING FACILITY	
LIQUID CONNECTION	STANDARD LPG BRASS FITTINGS WITH/CAP. THERE MAYBE SPECIAL REQUIREMENT TO BE RECEIVED FROM LOADING FACILITY. CONTACT LYONDELLBASELL FOR ANY SPECIAL REQUIREMENTS. PLEASE NOTE: SITE MAY REQUIRE KAMVALOK (DRY CONNECT) FITTING WITH CAP. PLEASE VERIFY ANY SPECIFIC REQUIREMENT PRIOR TO ARRIVAL FOR LOADING	
VAPOR CONNECTION	STANDARD LPG BRASS FITTINGS WITH/CAP. THERE MAYBE SPECIAL REQUIREMENT TO BE RECEIVED FROM LOADING FACILITY. CONTACT LYONDELLBASELL FOR ANY SPECIAL REQUIREMENTS. PLEASE NOTE: SITE MAY REQUIRE KAMVALOK (DRY CONNECT) FITTING WITH CAP. PLEASE VERIFY ANY SPECIFIC REQUIREMENT PRIOR TO ARRIVAL FOR LOADING	
NITROGEN PADDING	NITROGEN PURGED, (TRAILER MUST HAVE A 5-7 PSIG NITROGEN PAD UPON ARRIVAL)	
TANK CLEANLINESS	IF NOT DEDICATED TRAILER, A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. NOTE: IF TRAILER IS RE-LOAD, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS IS REQUIRED TO INDICATE THE SAME PRIOR PRODUCT	
STRAPPING CHART	YES	
HOSES	HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS OF THE LYONDELLBASELL SHIPPING DOCUMENT.	
ADDITIONAL APPURTENANCES	NONE, CARRIER SHOULD ALWAYS NOTE CARRIER'S INSTRUCTION FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENINGS TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL.	
OTHER	MUST HAVE SAP CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELLBASELL OF ANY REQUESTED LIGHT LOADING DUE TO POTENTIAL EXCEEDANCE LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS	
PROHIBITED	NO ADDITIONAL PERSONNEL, UNLESS TEAM DRIVERS, PETS ARE PROHIBITED.	