

	<p><b>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable</b></p>
<p><b>TANK TRAILER SPECIFICATION</b></p>	
<p><b>PRODUCT</b></p>	<p><b>PHENYL ETHYL ALCOHOL (PEA)</b></p>
<p><b>Material Characteristic and immediate hazard</b></p>	<p><b>See Product SDS</b></p>
<p><b>DOT SPECIFICATION</b></p>	<p>MC 307, DOT 407 (STAINLESS STEEL TRAILER)</p>
<p><b>INSULATION</b></p>	<p>PREFERRED BUT NOT REQUIRED</p>
<p><b>HEATING CAPABILITIES</b></p>	<p>NOT REQUIRED</p>
<p><b>GASKET MATERIAL</b></p>	<p>WHITE EPDM, VIRGIN TEFLON , TEFLON ROPE, TEFLON INCAPSULATED, **DOME GASKET MUST PROVIDE A LEAK TIGHT SEAL UPON COMPLETION OF LOADING</p>
<p><b>CONNECTIONS/FITTINGS</b></p>	<p>ALL MUST BE STAINLESS STEEL, W/DUST CAP, W/SEAL PONTS, DOME LID AND ALL OPENINGS TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL</p>
<p><b>LIQUID CONNECTION</b></p>	<p>3 "MALE CAMLOCK (QUICK CONNECT), W/DUST CAP - BOTTOM REAR LOADER (CENTER LOADER WILL REQUIRE APPROVAL). NOTE: CUSTOMER MAY HAVE SPECIFIC EQUIPMENT REQUIREMENTS FOR DELIVERY. MUST BE EQUIPPED FOR SEALING WITH AN 1/8" WIRE</p>
<p><b>VAPOR CONNECTION</b></p>	<p>2" MALE CAMLOCK (QUICK CONNECT), W/DUST CAP - VENT PIPING TO GRADE LEVEL, WITH 2" SS ISOLATION VALVE , (INLINE PRESSURE GAUGE @ GRADE LEVEL PREFERRED). 2" WITH DUST CAP, (MUST BE ABLE TO SEAL). NOTE: STANDARD 3/4" TOP CONNECTION MAYBE ACCEPTABLE WITH PRIOR APPROVAL</p>
<p><b>NITROGEN PADDING</b></p>	<p>5-7 PSIG NITROGEN PAD UPON ARRIVAL</p>
<p><b>TANK CLEANLINESS</b></p>	<p>CLEAN TRAILER MUST BE CLEAN, DRY, AND ODOR FREE. IF NOT A DEDICATED TRAILER, A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. NOTE: IF TRAILER IS RE-LOAD, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS IS REQUIRED TO INIDCATE THE SAME PRIOR PRODUCT</p>
<p><b>STRAPPING CHART W/DRIVER</b></p>	<p>YES</p>
<p><b>HOSES</b></p>	<p>HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS OF THE LYONDELLBASELL SHIPPING DOCUMENT.</p>
<p><b>ADDITIONAL APPURTENANCES</b></p>	<p>NONE, CARRIER SHOULD ALWAYS NOTE CARRIER'S INSTRUCTION FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENINGS TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL.</p>
<p><b>OTHER</b></p>	<p>MUST HAVE SAP CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELL OF ANY REQUESTED LIGHT LOADING DUE TO POTENTIAL EXCEEDING LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS</p>
<p><b>PROHIBITED</b></p>	<p>NO ADDITIONAL PERSONNEL, UNLESS TEAM DRIVERS, PETS ARE PROHIBITED</p>