

|   |  |  |
|---|--|--|
|  | <p><b>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable</b></p>   |  |
| <b>TANK TRAILER SPECIFICATION</b>   |  |  |
| <b>PRODUCT</b>  | <b>RESIDUAL FUEL OIL (635) RFO-635</b>   |  |
| <b>Material Characteristic and immediate hazard</b>                               | <b>See Product SDS</b>   |  |
| <b>DOT SPECIFICATION</b>  | MC 307, DOT 407 (STAINLESS STEEL TRAILER)  |  |
| <b>INSULATION</b>   | REQUIRED; NON INSULATED TRAILER REQUIRES PRIOR APPROVAL FROM LYONDELLBASELL BEFORE LOADING   |  |
| <b>HEATING CAPABILITIES</b>   | REQUIRED; NON HEATING CAPABILITIES REQUIRES APPROVAL   |  |
| <b>GASKET MATERIAL</b>  | VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, **DOME GASKET MUST GIVE A LEAK TIGHT SEAL UPON COMPLETION OF LOADING  |  |
| <b>CONNECTIONS/FITTINGS</b>   | ALL MUST BE STAINLESS STEEL, W/DUST CAP, W/SEAL PONTS ON ALL OUTLET OF TRAILER, CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL  |  |
| <b>LIQUID CONNECTION</b>  | 3" MALE CAMLOCK, (QUICK CONNECT), W/DUST CAP - BOTTOM REAR LOADER, (CENTER LOADER WILL REQUIRE APPROVAL). MUST HAVE SEALING CAPABILITIES. NOTE: CUSTOMER MAY HAVE SPECIFIC EQUIPMENT REQUIREMENTS. MUST HAVE SEAL POINTS   |  |
| <b>VAPOR CONNECTION</b>   | 2" MALE CAMLOCK (QUICK CONNECT), W/DUST CAP, WITH PIPING TO GRADE LEVEL, WITH 2" SS ISOLATION VALVE UPSTREAM OF FITTING, (INLINE PRESSURE GAUGE @ GRADE LEVEL PREFERRED). 2" WITH DUST CAP, (MUST BE ABLE TO SEAL), STANDARD 3/4" TOP VAPOR CONNTECTION IS ACCEPTABLE  |  |
| <b>NITROGEN PADDING</b>   | 5-7 PSIG PAD UPON ARRIVAL  |  |
| <b>TANK CLEANLINESS</b>   | IF NOT DEDICATED TRAILER, A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. A CLEAN TRAILER MUST BE CLEAN, DRY, AND ODOR FREE. NOTE: IF TRAILER IS RE-LOAD, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS ARE REQUIRED AS PROOF THAT THE LAST CONTAINED WAS LYONDELLBASELL LIKE MATERIAL.  |  |
| <b>STRAPPING CHART W/DRIVER</b>   | YES  |  |
| <b>HOSES</b>  | HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS OF THE LYONDELLBASELL SHIPPING  |  |
| <b>ADDITIONAL APPURTENANCES</b>   | NONE, CARRIER SHOULD ALWAYS NOTE CARRIER'S INSTRUCTION FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENING TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL.  |  |
| <b>OTHER</b>  | MUST HAVE SAP CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELLBASELL OF ANY REQUESTED LIGHT LOADING; DUE TO POTENTIAL EXCEEDANCE OF LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS |  |
| <b>PROHIBITED</b>   | NO ADDITIONAL PERSONNEL; UNLESS TEAM DRIVERS, PETS PROHIBITED  |  |