

	<p><b>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable</b></p>
<p><b>TANK TRAILER SPECIFICATION</b></p>	
<p><b>PRODUCT</b></p>	<p><b>TERT-BUTYL HYDROPEROXIDE (TBHP)</b></p>
<p><b>Material Characteristic and immediate hazard</b></p>	<p><b>See Product SDS</b></p>
<p><b>DOT SPECIFICATION: (NORTH AMERICA ONLY)</b></p>	<p>MC 312/DOT 412 - DEDICATED TO TERT-BUTYL HYDROPEROXIDE SERVICE AND DEDICATED TO A SINGLE CARRIER (DANA TRANSPORT) <b>DEDICATED TRAILERS #: D-792, D-793, D-4370, D-4371, D-4372, D-4373, D-4375.</b> ANY EQUIPMENT FOR TBHP SERVICES MUST BE APPROVED</p>
<p><b>INSULATION/HEATING</b></p>	<p>INSULATION REQUIRED; HEATING NOT REQUIRED</p>
<p><b>GASKET MATERIAL</b></p>	<p>TEFLON, KALREZ, OR SIMRIZ 7295 ONLY; MUST BE IN ALL FLANGES AND OPENING TO TRAILER</p>
<p><b>CONNECTIONS/FITTINGS</b></p>	<p>ALL MUST BE STAINLESS STEEL, DUST CAPS W/SEAL PONTS, ALL VALVES MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE</p>
<p><b>LIQUID CONNECTION</b></p>	<p>3" MALE KAMVALOK (DRY CONNECT), W/DUST CAP - LIQUID PIPING MODIFIED TO BOTTOM REAR GRADE LEVEL @ 90° ANGLE FOR LOADING. MUST HAVE 2 ISOLATION VALVES; 1 CLOSE TO TRAILER AND THE OTHER UPSTREAM OF THE LIQUID CONNECTION.</p>
<p><b>VAPOR CONNECTION</b></p>	<p>2" MALE KAMVALOK (DRY CONNECT), W/DUST CAP - VAPOR PIPING MODIFIED TO BOTTOM REAR GRADE LEVEL @ 90° ANGLE FOR VENTING W/PRESSURE GAUGE AND ISOLATION VALVE.</p>
<p><b>NITROGEN PADDING</b></p>	<p>YES, MINIMUM 15 PSIG ON CLEAN OR RE-LOAD UPON ARRIVAL</p>
<p><b>TANK CLEANLINESS</b></p>	<p>ALL TANK TRAILER SHOULD BE DEDICATED. IF A TANK TRAILER HAS TO BE CLEANED, A CLEANING CERTIFICATE MUST BE SENT WITH TRAILER. TRAILER MUST BE PROPERLY FILLED WITH SADDLES. <b>NOTE:</b> A MAINTENANCE CERTIFICATE MUST ALSO BE WITH TRAILER THAT INDICATED THE TYPE OF MAINTENANCE PERFORMED</p>
<p><b>STRAPPING CHART W/DRIVER</b></p>	<p>YES</p>
<p><b>HOSES</b></p>	<p>HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS OF THE LYONDELLBASELL SHIPPING</p>
<p><b>ADDITIONAL APPURTENANCES</b></p>	<p>DOME LID MUST BE A SOLID BOLTED FLANGE; TANK TRAILERS ARE CUSTOMED MODIFIED BY CARRIER. TRAILER MUST HAVE AN EMERGENCY SHUT-OFF ON LIQUID LINE NEAR TRAILER. <b>SPECIAL NOTE:</b> RETURN SEALS MUST BE SENT WITH DRIVER. DRIVER MUST ENSURE RETURN SEALS ARE INSTALLED EITHER BY DRIVER OR CUSTOMER. ALL FLANGES AND SCREWED FITTING MUST BE SEALED CLOSED. <b>TRAILER MUST BE EQUIPPED WITH TEMPERATURE GAUGE</b></p>
<p><b>OTHER</b></p>	<p>TRAILERS ARE TO BE TRANSPORTED BY DANA TRANSPORT DRIVERS ONLY. MUST HAVE SAP CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. <b>**DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME.</b> PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS. SPECAIL REQUIREMENT: TRAILER MUST HAVE THE PROPER AMOUNT OF SADDLES AND A VALID SP-6610 PERMIT</p>
<p><b>PROHIBITED</b></p>	<p><b>NOTE:</b> NO CUSTOMER PICKUP; TERT-BUTYL HYDROPEROXIDE WILL ONLY BE LOADED INTO LYONDELLBASELL DEDICATED TANK TRAILERS LISTED. NO PETS OR ADDITIONAL PERSONNEL UNLESS THEY ARE TEAM DRIVER. PETS ARE PROHIBITED</p>