

	<b>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable</b>	
<b>TANK TRAILER SPECIFICATION</b>		
<b>PRODUCT</b>	<b>TRIETHYLENE GLYCOL (ALL GRADES) (TEG)</b>	
<b>Material Characteristic and immediate hazard</b>	<b>See Product SDS</b>	
<b>DOT SPECIFICATION</b>	MC 307, DOT 407 (STAINLESS STEEL TRAILER); <b>IF NO PRODUCT HEATING IS REQUIRED</b> , MC 307, DOT 407 (ALUMINUM TRAILER) IS ACCEPTABLE	
<b>INSULATION</b>	PREFERRED; BUT NOT REQUIRED	
<b>HEATING CAPABILITIES</b>	NOT REQUIRED	
<b>GASKET MATERIAL</b>	VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, **DOME GASKET AND OTHER GASKETS, MUST PROVIDE A LEAK TIGHT SEAL PRE AND POST LOADING. ALL OPENING TO TRAILER MUST HAVE A SEAL POINT	
<b>CONNECTIONS/FITTINGS</b>	ALL MUST BE STAINLESS STEEL, W/DUST CAP, W/SEAL PONTS ON ALL OUTLET OF TRAILER, CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL (MUST HAVE SEAL POINTS).	
<b>LIQUID CONNECTION</b>	3" MALE CAMLOCK, (QUICK CONNECT), W/DUST CAP - BOTTOM REAR LOADER, (CENTER LOADER WILL REQUIRE APPROVAL). MUST HAVE SEALING CAPABILITIES. NOTE: CUSTOMER MAY HAVE SPECIFIC EQUIPMENT REQUIREMENTS. MUST HAVE SEAL POINTS	
<b>VAPOR CONNECTION</b>	2" MALE CAMLOCK (QUICK CONNECT), W/DUST CAP, WITH PIPING TO GRADE LEVEL, WITH 2" SS ISOLATION VALVE UPSTREAM OF FITTING, (INLINE PRESSURE GAUGE @ GRADE LEVEL PREFERRED). 2" WITH DUST CAP, (MUST BE ABLE TO SEAL), STANDARD 3/4" TOP VAPOR CONNTECTION MAYBE ACCEPTABLE	
<b>NITROGEN PADDING</b>	5-7 PSIG NITROGEN PAD UPON ARRIVAL	
<b>TANK CLEANLINESS</b>	IF NOT DEDICATED TRAILER, A CLEAN TRAILER MUST BE CLEAN, DRY, AND ODOR FREE. A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. NOTE: IF TRAILER IS RE-LOAD, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS IS REQUIRED TO INIDCATE THE SAME PRIOR LYONDELLBASELL PRODUCT	
<b>STRAPPING CHART W/DRIVER</b>	YES	
<b>HOSES</b>	HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS OF THE LYONDELLBASELL SHIPPING	
<b>ADDITIONAL APPURTENANCES</b>	NONE, CARRIER SHOULD ALWAYS NOTE CARRIER'S INSTRUCTION FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENING TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL.	
<b>OTHER</b>	MUST HAVE CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELLBASELL OF ANY REQUESTED LIGHT LOADING; DUE TO POTENTIAL EXCEEDANCE OF LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS	
<b>PROHIBITED</b>	NO ADDITIONAL PERSONNEL, UNLESS TEAM DRIVERS, PETS ARE PROHIBITED.	