

	These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable	
TANK TRAILER SPECIFICATION		
PRODUCT	ACETONE	
Material Characteristic and immediate hazard	See Product SDS	
DOT SPECIFICATION	MC 307, DOT 407 (STAINLESS STEEL TRAILER)	
INSULATION	PREFERRED, BUT NOT REQUIRED	
HEATING CAPABILITIES	NOT REQUIRED	
GASKET MATERIAL	TEFLON ROPE, VIRGIN TEFLON, TEFLON ENCAPSULATED , **DOME GASKET MUST GIVE A LEAK TIGHT SEAL UPON COMPLETION OF LOADING	
CONNECTIONS/FITTINGS	ALL MUST BE STAINLESS STEEL, W/DUST CAP, W/SEAL PONTS, DOME LID AND ALL OPENINGS TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL, DUST CAPS W/SEAL PONTS, DOME LID ATTACHMENTS FOR PROPER SEALING	
LIQUID CONNECTION	3 "MALE CAMLOCK (QUICK CONNECT), W/DUST CAP -- BOTTOM REAR LOADER (CENTER LOADER WILL REQUIRE APPROVAL FROM LYONDELLBASELL). NOTE: CUSTOMER MAY HAVE SPECIFIC EQUIPMENT REQUIREMENTS FOR DELIVERY, LISTED IN THE <i>CARRIER INSTRUCTIONS</i> FIELD OF THE SHIPPING DOCUMENT. MUST BE EQUIPPED FOR SEALING WITH A 1/8" WIRE CABLE SEAL.	
VAPOR CONNECTION	2" MALE CAMLOCK (QUICK CONNECT), W/DUST CAP, WITH PIPING TO GRADE LEVEL, WITH 2" SS ISOLATION VALVE, (INLINE PRESSURE GAUGE @ GRADE LEVEL PREFERRED). 2" W/DUST CAP, (MUST BE ABLE TO SEAL). STANDARD 3/4" TOP CONNECTION MAYBE ACCEPTABLE WITH PRIOR APPROVAL FROM LYONDELLBASELL.	
NITROGEN PADDING	TRAILER MUST HAVE 5-7 PSIG NITROGEN PAD FOR MOISTURE AND FLAMMABLE ATMOSPHERE CONTROL, UPON ARRIVAL FOR LOADING	
TANK CLEANLINESS	CLEAN TRAILER MUST BE CLEAN, DRY, AND ODOR FREE. IF NOT A DEDICATED TRAILER, A CLEANING OR RE-LOAD/TOP-LOAD CERTIFICATE IS REQUIRED. NOTE: IF TRAILER IS RE-LOAD/TOP-LOAD, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS ARE REQUIRED AS PROOF THAT THE LAST CONTAINED WAS LYONDELLBASELL MATERIAL	
STRAPPING CHART W/DRIVER	YES	
HOSES	HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR DELIVERY-CUSTOMER THAT SHOULD BE NOTED IN THE <i>CARRIER INSTRUCTIONS</i> FIELD OF THE LYONDELLBASELL SHIPPING DOCUMENT.	
ADDITIONAL APPURTENANCES	NONE, CARRIER SHOULD ALWAYS NOTE <i>CARRIER INSTRUCTIONS</i> FIELD FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENINGS TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL.	
OTHER	MUST HAVE SAP CURRENT AND MATCHING SAP <i>SHIPPING NOTICE</i> , <i>TRANSWIDE CALL-OFF</i> , OR <i>CARRIER MANIFEST</i> DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELL OF ANY REQUESTED LIGHT LOADING DUE TO POTENTIAL EXCEEDING LEGAL GROSS WEIGHT OR VARIANCE FROM CUSTOMER ORDERED-QUANTITY. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS.	
PROHIBITED	NO ADDITIONAL PERSONNEL UNLESS TEAM DRIVERS, PETS PROHIBITED	