



These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable

TANK TRAILER SPECIFICATION

PRODUCT **TERT-BUTYL ACETATE (TBAC)**

Material Characteristic and immediate hazard	See Product SDS
DOT SPECIFICATION	MC 307, MC 407, DOT 307, DOT 407 (STAINLESS STEEL TRAILER)
INSULATION	REQUIRED
HEATING CAPABILITIES	NOT REQUIRED
GASKET MATERIAL	VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, KALREZ; DOME GASKET MUST PROVIDE A LEAK TIGHT SEAL PRE AND POST LOADING.
CONNECTIONS/FITTINGS	MUST BE STAINLESS STEEL, W/ DUST CAPS, W/ SEAL PONTS ON ALL OUTLETS OF TRAILER; ALL OUTLETS AND OPENINGS MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL.
LIQUID CONNECTION	3" MALE CAMLOCK (DRY DISCONNECT), W/ DUST CAP - BOTTOM REAR LOADER @ 90° ANGLE, (IN-LOADER OR CENTER LOADER WILL REQUIRE APPROVAL BY LYONDELLBASELL). MUST HAVE SEAL POINTS. NOTE: CUSTOMER MAY HAVE SPECIFIC EQUIPMENT REQUIREMENTS.
VAPOR CONNECTION	2" MALE CAMLOCK (DRY DISCONNECT), GRADE LEVEL VAPOR LINE WITH 2" SS ISOLATION VALVE, WITH INLINE PRESSURE GAUGE @ GRADE LEVEL. 2" DUST CAP, MUST BE ABLE TO SEAL.
NITROGEN PADDING	NITROGEN PURGED; TRAILER MUST HAVE A 5-7 PSIG PAD UPON ARRIVAL TO LOAD; TRAILER MUST PROVIDE A LEAK FREE SEAL PRE AND POST LOADING
TANK CLEANLINESS	IF NOT DEDICATED TRAILER, A CLEAN TRAILER MUST BE CLEAN, DRY, AND ODOR FREE. A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. NOTE: IF TRAILER IS RE-LOAD, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS IS REQUIRED TO INDICATE THE SAME PRIOR LYONDELLBASELL PRODUCT
STRAPPING CHART W/DRIVER	YES
HOSES	HOSES ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS OF THE LYONDELLBASELL SHIPPING DOCUMENT.
ADDITIONAL APPURTENANCES	CARRIER SHOULD ALWAYS NOTE CARRIER INSTRUCTION FIELD OF THE LYONDELLBASELL SHIPPING DOCUMENT FOR ANY ADDITIONAL EQUIPMENT REQUIREMENTS, DRIVER REQUIREMENTS, ETC.
OTHER	MUST HAVE CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. DRIVER MUST ALWAYS NOTIFY LYONDELLBASELL OF ANY REQUESTED LIGHT LOADING DUE TO POTENTIAL EXCEEDANCE OF LEGAL GROSS WEIGHT.
PROHIBITED	NO ADDITIONAL PERSONNEL ALLOWED UNLESS TEAM DRIVERS; PETS ARE PROHIBITED.